

ROTARY TILLERS



ZLL SERIES

20-35 HP - 43", 51", 60"

- Center working position
- #80 chain drive
- Slip clutch PTO
- 6" tilling depth, 6 blades per flange

SB SERIES

20-35 HP - 39", 43", 51", 55"

- Manual offset 12" to 20" depending on model
- #80 chain drive
- Slip clutch PTO
- 6" tilling depth, 6 blades per flange



SF SERIES

20-50 HP - 49", 57", 65", 73"

- Manual offset 15" to 26" depending on model
- All gear drive
- Slip clutch PTO
- 7" tilling depth, 6 blades per flange



CS SERIES

25-50 HP - 33", 41", 49", 57", 65", 73"

- Center working position
- All gear drive
- Slip clutch PTO
- 7" tilling depth, 6 blades per flange



ROTARY TILLERS



ST SERIES

35-60 HP - 61", 72", 81"

- Center working position
- All gear drive, 4-speed gear box
- Slip clutch PTO
- 8" tilling depth, 6 blades per flange

SP SERIES

60-90 HP - 71", 81", 91", 100"

- 4-speed gear box
- All gear drive
- Slip clutch PTO
- 8" tilling depth, 6 blades per flange



RG SERIES

90-160 HP - 90", 100", 120"

- 2 + 2 speed gear box
- All gear drive
- Slip clutch PTO
- 10" tilling depth, 6 blades per flange
- Optional Equipment: Cage Rollers

